SAMEDI 27 XROAD 1



FRAME
Xroad, 6061 T4-T6 alloy, variable thickness hydroformed tubes, Bosch PowerTube battery integration (vertical), integrated cable routing

SEATCLAMP
Moustache, alloy, 34.9mm

HEADSET
FSA, No 57B-1

FORK
SR Suntour, XCM ATB, preload adjustment, 80mm travel

MOTOR
Bosch, Active Line Plus, 250W, 35/50Nm

BATTERY
Bosch, PowerTube 400Wh, vertical

DISPLAY
Bosch, Purion - « Walk assist »

CHARGER
Bosch, 2Ah

RIMS
Moustache, asymmetric, alloy 6061E, welded, 32 holes, 27.5", internal width 23mm

FRONT HUB
Shimano, 32H, 9x100mm, QR (Quick Release)

TYRES
Hutchinson, Python 2, 27.5x2.10

REAR HUB
Shimano, 32H, 9x135mm, QR (Quick Release)

STEM
Moustache, alloy, adjustable, 90mm

HANDLEBAR
Moustache, ergonomic, alloy, 680mm, 25° backsweep

GRIPS
Ergonomic, dual-density

SADDLE
Selle Royal, Wave

SEATPOST
Moustache, alloy, 31.6mm, 350mm

CASSETTE
Shimano, CS-HG201, 9-speed, 11-36T

CHAIN
KMC, X9, 9-speed, 120 links

REAR DERAILLEUR
Shimano, Altus, RD-R2000-SGS, 9-speed

SHIFTER
Shimano, Altus, SL-M2010-R, 9-speed

CRANKS
Moustache, aluminium, 170mm

CHAINRING
Narrow-Wide, 40 teeth

PEDALS
Resin platform with reflectors

FRONT BRAKE
Shimano, MT200 or Alhonga HJ-472, hydraulic disc brake

FRONT ROTOR
Shimano, 180mm or Alhonga, 180mm

REAR BRAKE
Shimano, MT200 or Alhonga HJ-472, hydraulic disc brake

REAR ROTOR
Shimano, 160mm or Alhonga, 160mm

FRONT LIGHT
AXA, Blueline, 30 lux, powered by main battery

REAR LIGHT
Spanninga, Presto2Guard, powered by main battery

MUDGUARD
Moustache, alloy, double wall design, w/alloy stays

CARRIER
Moustache, alloy, removable QL3 lateral fixation, MIK HD platform

KICKSTAND
Moustache, adjustable

AUTONOMY
99km

GVWR
135kg

WEIGHT
25kg

SIZES
S (1,55 -1,70m) M (1,68 - 1,83m) L (1,80 - 1,95m) XL (1,90 - 2,05m)

COLORS
Pastel Green glossy

CONDITIONS
Maximum distance, calculated for a 70kg rider in ideal conditions. Estimate your battery range .


WARRANTY
5 years frame and fork Moustache Bikes - 2 years motor, battery

Scan to find this bike online

MOUSTACHE

SAMEDI 27
XROAD 1





TAILLE - ST	mm	420 (S)	470 (M)	530 (L)	580 (XL)
Taille utilisateur (à titre indicatif)	m	1,55 - 1,70	1,68 - 1,83	1,80 - 1,95	1,90 - 2,05
Tube supérieur (mesure horizontale) - TT	mm	560	585	610	635
Bases - RC	mm	475	475	475	475
Douille de direction - HT	mm	170	170	170	190
Empattement - WB	mm	1108	1123	1148	1174
Longueur de fourche - FL	mm	487	487	487	487
Hauteur boitier - BB	mm	298	298	298	298
Angle de selle - SA	°	71	71	71	71
Angle de direction - HA	°	67,2	68	68	68
Reach	mm	341	365	390	409
Stack	mm	644	648	648	667

Scan to find this bike online

TOUSTACHE