SAMEDI 27 XROAD 3



FRAME
Xroad, 6061 T4-T6 Alloy, variable thickness hydroformed tubes, Bosch PowerTube battery integration (vertical), integrated cable routing

FORK
Suntour, XCM ATB, HLO w/preload adjustment & lockout function, 80mm travel

MOTOR
Bosch, Performance Line 250W - 35/65 Nm - Assistance from 55 to 300 % - 25 km/h - Natural - Noise free - Frictionless - Compact - Lightweight

BATTERY
Bosch, PowerTube 625Wh

BATTERY RANGE
Up to 177jm. Estimate your ebike battery range

CHARGER
Bosch, 4Ah

DISPLAY
Bosch, Purion - 5 modes (Eco, Tour, Sport, Turbo, Off) - « Walk assist »

REAR DERAILLEUR
Shimano, Deore, RD-M4120-SGS, 10-speed

FRONT COG / CHAINRING
Samox, Alloy, 40T w/chainguard

CASSETTE
Sunrace, CSMS2, 11-42T

CHAIN
KMC, X10, 10-speed

SHIFTERS
Shimano, Deore, Rapidfire Plus for flat handlebar

CRANKSET
Moustache, Alloy, 170mm

BRAKES
Shimano, MT200 hydraulic disc brakes or Alhonga brake, HJ-472 (depending on supply)

ROTORS FRONT/REAR (IN MM)
Shimano, 180mm front & 160mm rear

HUBS
Front= Shimano, 32H, 9x100mm, w/QR Rear= Shimano, 32H, 9x135mm, w/QR

RIMS
Moustache, Alloy, double wall, 32H

TIRES
Hutchinson, Python, 27.5x2.10

SADDLE
Selle Royal, Shadow Ergonomic

SEATPOST
Suspension, Alloy 31.6mm, 350mm, 40mm travel

SEAT CLAMP
Moustache, Alloy, 34.9mm

HANDLEBAR
Moustache, Ergonomic, Alloy, 680mm, 25° backsweep

STEM
Moustache, Alloy, 90mm Adjustable

HEADSET
FSA, No 57-B

GRIPS
Ergonomic, dual-density

HEADLIGHT
AXA, Blueline, 30 lux, powered by main battery

TAILLIGHT
Spanninga, Presto2Guard, powered by main battery

KICKSTAND
Moustache, adjustable

MUDGUARDS
Moustache, Alloy, double wall design, w/alloy stays

REAR CARRIER
Moustache, Alloy, QL3 low-rider carrier, MIK Bag/Accessories compatible

PEDALS
Resin with plateform and reflectors

WARRANTY
5 years frame and Moustache Bikes fork - 2 years motor, battery (or 500 cycles) and accessories

SIZES
Small, Medium, Large, X-Large

COLOR
White Grey, glossy

TOTAL WEIGHT AUTHORIZED
135 kg


WEIGHT
25.7 kg

Scan to find this bike online

MOUSTACHE

SAMEDI 27
XROAD 3





TAILLE - ST	mm	420 (S)	470 (M)	530 (L)	580 (XL)
Taille utilisateur (à titre indicatif)	m	1,55 - 1,70	1,68 - 1,83	1,80 - 1,95	1,90 - 2,05
Tube supérieur (mesure horizontale) - TT	mm	560	585	610	635
Bases - RC	mm	475	475	475	475
Douille de direction - HT	mm	170	170	170	190
Empattement - WB	mm	1108	1123	1148	1174
Longueur de fourche - FL	mm	487	487	487	487
Hauteur boitier - BB	mm	298	298	298	298
Angle de selle - SA	°	71	71	71	71
Angle de direction - HA	°	67,2	68	68	68
Reach	mm	341	365	390	409
Stack	mm	644	648	648	667

Scan to find this bike online

{TOUSTACHE