# SAMEDI 28.1



**FRAME**
Samedi 28, 6061 T4-T6 alloy, variable thickness extruded tubes, headtube 1"1/8

**SEATCLAMP**
Moustache, alloy, 31.8mm

**HEADSET**
FSA, No 10P

**FORK**
SR Suntour, NEX-E25, 63mm travel

**MOTOR**
Bosch, Active Line, 250W, 40Nm

**BATTERY**
Bosch, PowerPack 400Wh

**DISPLAY**
Bosch, Purion - « Walk assist »

**CHARGER**
Bosch, 2Ah

**RIMS**
Moustache, asymmetric, alloy 6061E, welded, 32 holes, 28", internal width 23mm

**FRONT HUB**
Shimano, 32H, 9x100mm, QR (Quick Release)

**TYRES**
Schwalbe, Impac Streetpac, 700x47c

**REAR HUB**
Shimano, 32H, 9x135mm, QR (Quick Release)

**HANDLEBAR**
Moustache, ergonomic, alloy, 80mm rise

**GRIPS**
Ergonomic, dual-density

**SADDLE**
Selle Royal, Wave

**SEATPOST**
Moustache, alloy, 31.6mm, 350mm

**CASSETTE**
Shimano, CS-HG201, 9-speed, 11-36T

**CHAIN**
KMC, X9, 9-speed, 120 links

**REAR DERAILLEUR**
Shimano, Altus, RD-R2000-SGS, 9-speed

**SHIFTER**
Shimano, Altus, SL-M2010-R, 9-speed

**CRANKS**
Moustache, aluminium, 170mm

**CHAINRING**
Narrow-Wide, 40 teeth

**PEDALS**
Resin platform with reflectors

**FRONT BRAKE**
Shimano, MT200 or Alhonga HJ-472, hydraulic disc brake

**FRONT ROTOR**
Shimano, 180mm or Alhonga, 180mm

**REAR BRAKE**
Shimano, MT200 or Alhonga HJ-472, hydraulic disc brake

**REAR ROTOR**
Shimano, 160mm or Alhonga, 160mm

**FRONT LIGHT**
AXA, Blueline, 30 lux, powered by main battery

**REAR LIGHT**
Spanninga, Presto2Guard, powered by main battery

**MUDGUARD**
Moustache, alloy, double wall design, w/alloy stays

**CARRIER**
Moustache, alloy, removable QL3 lateral fixation

**KICKSTAND**
Moustache, adjustable

**AUTONOMY**
108km

**GVWR**
135kg

**WEIGHT**
22.8kg

**SIZES**
S (1,55 -1,70m) M (1,68 - 1,83m) L (1,80 - 1,95m) XL (1,90 - 2,05m)

**COLORS**
Black mat

**CONDITIONS**
Maximum distance, calculated for a 70kg rider in ideal conditions. Estimate your battery range .


**WARRANTY**
5 years frame and fork Moustache Bikes - 2 years motor, battery

**Scan to find this bike online**

MOUSTACHE

# SAMEDI 28.1






| TAILLE - ST | mm | 410 (S) | 470 (M) | 530 (L) | 590 (XL) |
|---|---|---|---|---|---|
| Taille utilisateur (à titre indicatif) | m | 1,55 - 1,70 | 1,66 - 1,83 | 1,81 - 1,95 | 1,90 - 2,05 |
| Tube supérieur (mesure horizontale) - TT | mm | 560 | 585 | 610 | 635 |
| Bases - RC | mm | 470 | 470 | 470 | 470 |
| Douille de direction - HT | mm | 140 | 150 | 170 | 180 |
| Empattement - WB | mm | 1092 | 1112 | 1132 | 1158 |
| Longueur de fourche - FL | mm | 467 | 467 | 467 | 467 |
| Hauteur boitier - BB | mm | 60 | 60 | 60 | 60 |
| Angle de selle - SA | ° | 72 | 72 | 72 | 72 |
| Angle de direction - HA | ° | 68,5 | 69 | 69,5 | 69,5 |
| Reach | mm | 361 | 383 | 400 | 423 |
| Stack | mm | 610 | 623 | 644 | 653 |

**Scan to find this bike online**

MOUSTACHE