SAMEDI 28.1 OPEN



FRAME
Samedi 28 Open, 6061 T4-T6 alloy, variable thickness extruded tubes, headtube 1"1/8

SEATCLAMP
Moustache, alloy, 31.8mm

HEADSET
FSA, No 10P

FORK
SR Suntour, NEX-E25, 63mm travel

MOTOR
Bosch, Active Line, 250W, 40Nm

BATTERY
Bosch, PowerPack 400Wh

DISPLAY
Bosch, Purion - « Walk assist »

CHARGER
Bosch, 2Ah

RIMS
Moustache, asymmetric, alloy 6061E, welded, 32 holes, 28", internal width 23mm

FRONT HUB
Shimano, 32H, 9x100mm, QR (Quick Release)

TYRES
Schwalbe, Impac Streetpac, 700x47c

REAR HUB
Shimano, 32H, 9x135mm, QR (Quick Release)

HANDLEBAR
Moustache, ergonomic, alloy, 80mm rise

GRIPS
Ergonomic, dual-density

SADDLE
Selle Royal, Wave

SEATPOST
Moustache, alloy, 31.6mm, 350mm

CASSETTE
Shimano, CS-HG201, 9-speed, 11-36T

CHAIN
KMC, X9, 9-speed, 120 links

REAR DERAILLEUR
Shimano, Altus, RD-R2000-SGS, 9-speed

SHIFTER
Shimano, Altus, SL-M2010-R, 9-speed

CRANKS
Moustache, aluminium, 170mm

CHAINRING
Narrow-Wide, 40 teeth

PEDALS
Resin platform with reflectors

FRONT BRAKE
Shimano, MT200 or Alhonga HJ-472, hydraulic disc brake

FRONT ROTOR
Shimano, 180mm or Alhonga, 180mm

REAR BRAKE
Shimano, MT200 or Alhonga HJ-472, hydraulic disc brake

REAR ROTOR
Shimano, 160mm or Alhonga, 160mm

FRONT LIGHT
AXA, Blueline, 30 lux, powered by main battery

REAR LIGHT
Spanninga, Presto2Guard, powered by main battery

MUDGUARD
Moustache, alloy, double wall design, w/alloy stays

CARRIER
Moustache, alloy, removable QL3 lateral fixation

KICKSTAND
Moustache, adjustable

AUTONOMY
108km

GVWR
135kg

WEIGHT
22.8kg

SIZES
S (1,49 -1,61m) M (1,59 - 1,76m) L (1,74 - 1,90m)

COLORS
Black mat

CONDITIONS
Maximum distance, calculated for a 70kg rider in ideal conditions. Estimate your battery range .


WARRANTY
5 years frame and fork Moustache Bikes - 2 years motor, battery

Scan to find this bike online

MOUSTACHE

SAMEDI 28.1
OPEN





TAILLE - ST	mm	390 (S)	450 (M)	510 (L)
Taille utilisateur (à titre indicatif)	m	1,49 - 1,61	1,59 - 1,76	1,74 - 1,90
Tube supérieur (mesure horizontale) - TT	mm	550	575	600
Bases - RC	mm	470	470	470
Douille de direction - HT	mm	140	150	160
Empattement - WB	mm	1088	1105	1124
Longueur de fourche - FL	mm	467	467	467
Hauteur boitier - BB	mm	60	60	60
Angle de selle - SA	°	72,3	72	72
Angle de direction - HA	°	68,3	68,7	69,3
Reach	mm	355	373	394
Stack	mm	611	622	634

Scan to find this bike online

MOUSTACHE