SAMEDI 28.2 OPEN



FRAME
Samedi 28 Open, 6061 T4-T6 alloy, variable thickness hydroformed tubes, Bosch PowerTube battery integration (Vertical), integrated cable routing

SEATCLAMP
Moustache, alloy, 34.9mm

HEADSET
FSA, No 57B-1

FORK
SR Suntour, NEX-E25, 63mm travel

MOTOR
Bosch, Active Line Plus, 250W, 35/50Nm

BATTERY
Bosch, PowerTube 500Wh, vertical

DISPLAY
Bosch, Purion - « Walk assist »

CHARGER
Bosch, 4Ah

RIMS
Moustache, asymmetric, alloy 6061E, welded, 32 holes, 28", internal width 23mm

FRONT HUB
Shimano, 32H, 9x100mm, QR (Quick Release)

TYRES
Schwalbe, Big Apple, 700x50C

REAR HUB
Shimano, 32H, 9x135mm, QR (Quick Release)

HANDLEBAR
Moustache, ergonomic, alloy, 80mm rise

GRIPS
Ergonomic, dual-density

SADDLE
Selle Royal, Wave

SEATPOST
Suspension, alloy, 31.6mm, 350mm, 40mm travel

CASSETTE
Shimano, CS-HG201, 9-speed, 11-36T

CHAIN
KMC, X9, 9-speed, 120 links

REAR DERAILLEUR
Shimano, Altus, RD-R2000-SGS, 9-speed

SHIFTER
Shimano, Altus, SL-M2010-R, 9-speed

CRANKS
Moustache, aluminium, 170mm

CHAINRING
Narrow-Wide, 40 teeth

PEDALS
Resin platform with reflectors

FRONT BRAKE
Shimano, MT200 or Alhonga HJ-472, hydraulic disc brake

FRONT ROTOR
Shimano, 180mm or Alhonga, 180mm

REAR BRAKE
Shimano, MT200 or Alhonga HJ-472, hydraulic disc brake

REAR ROTOR
Shimano, 160mm or Alhonga, 160mm

FRONT LIGHT
AXA, Blueline, 30 lux, powered by main battery

REAR LIGHT
Spanninga, Presto2Guard, powered by main battery

MUDGUARD
Moustache, alloy, double wall design, w/alloy stays

CARRIER
Moustache, alloy, removable QL3 lateral fixation, MIK HD platform

KICKSTAND
Moustache, adjustable

AUTONOMY
137km

GVWR
135kg

WEIGHT
24.5kg

SIZES
S (1,49 -1,61m) M (1,59 - 1,76m) L (1,74 - 1,90m)

COLORS
Deep blue glossy

CONDITIONS
Maximum distance, calculated for a 70kg rider in ideal conditions. Estimate your battery range .


WARRANTY
5 years frame and fork Moustache Bikes - 2 years motor, battery

Scan to find this bike online

MOUSTACHE

SAMEDI 28.2 OPEN





TAILLE - ST	mm	390 (S)	450 (M)	510 (L)
Taille utilisateur (à titre indicatif)	m	1,49 - 1,61	1,59 - 1,76	1,74 - 1,90
Tube supérieur (mesure horizontale) - TT	mm	555	580	605
Bases - RC	mm	475	475	475
Douille de direction - HT	mm	170	170	170
Empattement - WB	mm	1101	1115	1124
Longueur de fourche - FL	mm	477	477	477
Hauteur boitier - BB	mm	305	305	305
Angle de selle - SA	°	71,5	71,5	71,5
Angle de direction - HA	°	67,7	68,5	68,5
Reach	mm	342	366	390
Stack	mm	644	644	644

Scan to find this bike online

MOUSTACHE