

DIMANCHE 28

ROAD 2

D82OGM400260



Product specifications may change without notice. Non-contractual information.

FRAME Dimanche 28 Open, 6061 T4-T6 alloy, variable thickness hydroformed tubes, CompactTube integration and internal cable routing	FRONT BRAKE Shimano, MT200/UR300, hydraulic disc	SADDLE Selle Royal, VIVO
FORK Dimanche 29/28, alloy, tapered steerer tube 1"1/8-1"1/2 - FlatMount 180mm direct brake mount - 15x100mm Axle - 45mm offset - For tires in 700x50 - Mounts for mud-guard and luggage racks	REAR BRAKE Shimano, MT200, hydraulic disc	SEATPOST Moustache, alloy, 27.2mm, 350mm
MOTOR Bosch, Performance Line SX, Smart System, 60Nm	FRONT ROTOR Shimano, 180mm	SEATCLAMP Moustache, alloy, 34.9mm
BATTERY Bosch, CompactTube 400Wh, Smart System	REAR ROTOR Shimano, 160mm	FRONT LIGHT -
CHARGER Bosch, 2Ah	FRONT HUB Moustache, 24H, 12x100mm, thru axle	PEDALS alloy platform with reflectors
REMOTE Bosch, Purion 200, Smart System	REAR HUB Moustache, 24H, 12x142mm, thru axle	SIZE M
BCM Not equipped with Bosch ConnectModule	FRONT RIM Moustache, al:30, alloy 6061, welded, 24 holes, 700c, 22mm internal width	COLOR Blue Grey glossy
RANGE AUTONOMY 116 km	REAR RIM Moustache, al:30, alloy 6061, welded, 24 holes, 700c, 22mm internal width	WEIGHT 17.5 kg
REAR DERAILLEUR Shimano, CUES, RD-U6000-GS, 10/11-speed	FRONT TYRE Hutchinson, Overide, 700x38	GVWR 120 kg
CHAINRING FSA, Narrow-Wide, 42 teeth, chainguard	REAR TYRE Hutchinson, Overide, 700x38	WARRANTY 5 years frame and fork Moustache Bikes - 2 years motor, battery
CASSETTE Shimano, CUES, CS-LG300 10-speed, 11-48T	HANDLEBAR Moustache, alloy, 680mm, 12mm rise, 9° backsweep, 5° upsweep	
CHAIN Shimano, LG500, 120 links	STEM Moustache, aluminium, suspended 10-20mm travel, 90mm	
SHIFTER Shimano, CUES, SL-U6000-10R, 10-speed	HEADSET Acros, AZF-725, sealed bearings, internal routing	
CRANKS Moustache, forged aluminium, 165mm	GRIPS SB3, Ergonomic	




Find this bike online

{MOUSTACHE

DIMANCHE 28

ROAD 2

D82OGM400260



Dimanche 28 Road 2/4 Open - Dimanche 29 Gravel 2/4 Open

ST - Taille / Size	mm	430 (XS)	460 (S)	500 (M)
Taille utilisateur / User size	m	1,43 - 1,55	1,53 - 1,68	1,66 - 1,81
TT - Tube supérieur / Top tube	mm	535	545	565
RC - Bases / Rear center	mm	437	437	437
HT - Douille de direction / Headtube	mm	120	120	135
WB - Empattement / Wheelbase	mm	1039	1039	1049
FL - Longueur de fourche / Fork length	mm	415	415	415
BB - Hauteur de boîtier / BB height	mm	288,5	288,5	288,5
SA - Angle de selle / Seat angle	°	73,6	73,3	73
HA - Angle de direction / Head angle	°	69,3	70	70,7
Reach	mm	369	375	386
Stack	mm	566	569	586
SO - Enjambement / Standover	mm	662	664	680



Find this bike online

{NOUSTACHE