

DIMANCHE 28

ROAD 2 2025

DI28C0254240



Product specifications may change without notice. Non-contractual information.

FRAME

Dimanche 28, 6061 T4-T6 alloy, variable thickness hydroformed tubes, CompactTube integration and internal cable routing

FORK

Dimanche 28, full carbon, tapered steerer tube 1"1/8-1"1/2, FlatMount 160mm direct brake mount, 12x100mm axle, 50mm offset, for tires in 700x45, mounts for mudguard

MOTOR

Bosch, Performance Line SX, Smart System, 60Nm

BATTERY

Bosch, CompactTube 400Wh, Smart System

CONDITIONS

Maximum distance, calculated for a 70kg rider in ideal conditions. Estimate your battery range .

CHARGER

Bosch, 2Ah

REMOTE

Bosch, Purion 200, Smart System

RANGE AUTONOMY

116 km

REAR DERAILLEUR

Shimano, CUES, RD-U6000-GS, 10/11-speed

CHAINRING

FSA, Narrow-Wide, 42 teeth, chainguard

CASSETTE

Shimano, CUES, CS-LG300 10-speed, 11-48T

CHAIN

Shimano, LG500, 130 links

SHIFTER

Shimano, CUES, SL-U6000-10R, 10-speed

CRANKS

Moustache, forged aluminium, 165mm

FRONT BRAKE

Shimano, MT200/UR300, hydraulic disc

REAR BRAKE

Shimano, MT200, hydraulic disc

FRONT ROTOR

Shimano, 160mm

REAR ROTOR

Shimano, 160mm

FRONT HUB

Moustache, 24H, 12x100mm, thru axle

REAR HUB

Moustache, 24H, 12x142mm, thru axle

FRONT RIM

Moustache, al:30, alloy 6061, welded, 24 holes, 700c, 22mm internal width

REAR RIM

Moustache, al:30, alloy 6061, welded, 24 holes, 700c, 22mm internal width

FRONT TYRE

Hutchinson, Override, 700x38

REAR TYRE

Hutchinson, Override, 700x38

HANDLEBAR

Moustache, alloy, 680mm, 12mm rise, 9° backsweep, 5° upsweep

STEM

Moustache, aluminium, suspended 10-20mm travel, 90mm

HEADSET

Acros, AZF-725, sealed bearings, internal routing

GRIPS

SB3, Ergonomic

SADDLE

Selle Royal, VIVO

SEATPOST

Moustache, alloy, 27.2mm, 350mm

SEATCLAMP

Moustache, alloy, 34.9mm

FRONT LIGHT

-

PEDALS

alloy platform with reflectors

SIZE

L

COLOR

Sand Storm matt

WEIGHT

17.3 kg

GVWR

120 kg

WARRANTY

5 years frame and fork Moustache Bikes - 2 years motor, battery




Find this bike online

{MOUSTACHE

DIMANCHE 28

ROAD 2 2025

DI28C0254240



Dimanche 28 Road 2/4/6 - Dimanche 29 Gravel 2/4/6

ST - Taille / Size	mm	460 (S)	500 (M)	540 (L)	580 (XL)
Taille utilisateur / User size	m	1,53 - 1,68	1,66 - 1,81	1,79 - 1,94	1,92 - 2,07
TT - Tube supérieur / Top tube	mm	545	565	585	605
RC - Bases / Rear center	mm	437	437	437	437
HT - Douille de direction / Headtube	mm	120	135	160	180
WB - Empattement / Wheelbase	mm	1039	1049	1061	1071
FL - Longueur de fourche / Fork length	mm	415	415	415	415
BB - Hauteur de boîtier / BB height	mm	288,5	288,5	288,5	288,5
SA - Angle de selle / Seat angle	°	73,3	73	72,8	72,5
HA - Angle de direction / Head angle	°	70	70,7	71,3	72
Reach	mm	375	386	395	405
Stack	mm	569	586	612	634
SO - Enjambement / Standover	mm	772	800	830	850



Find this bike online

{NOUSTACHE