SAMEDI 28.1 2021

SA28C0159215

Product specifications may change without notice. Non-contractual information.

FRAME
Samedi 28, 6061 T4-T6 alloy, variable thickness extruded tubes, headtube 1"1/8

FORK
SR Suntour, NEX-E25, 63mm travel

MOTOR
Bosch, Active Line, 40Nm

BATTERY
Bosch, PowerPack 500Wh

CONDITIONS
Maximum distance, calculated for a 70kg rider in ideal conditions. Estimate your battery range .

CHARGER
Bosch, 2Ah

DISPLAY
Bosch, Intuvia

RANGE AUTONOMY
108 km

REAR DERAILLEUR
Shimano, Altus, RD-R2000-SGS, 9-speed

CHAINRING
Narrow-Wide, 40 teeth

CASSETTE
Shimano, CS-HG201, 9-speed, 11-36T

CHAIN
KMC, X9, 9-speed, 120 links

SHIFTER
Shimano, Altus, SL-M2010-R, 9-speed

CRANKS
Moustache, aluminium, 170mm moteur Gen3

FRONT BRAKE
Shimano, MT200 or Alhonga HJ-472, hydraulic disc brake

REAR BRAKE
Shimano, MT200 or Alhonga HJ-472, hydraulic disc brake

FRONT ROTOR
Shimano, 180mm or Alhonga, 180mm

REAR ROTOR
Shimano, 160mm or Alhonga, 160mm

FRONT HUB
Shimano, 32H, 9x100mm, QR (Quick Release)

REAR HUB
Shimano, 32H, 9x135mm, QR (Quick Release)

FRONT RIM
Moustache, asymmetric, alloy 6061E, welded, 32 holes, 28", internal width 23mm

REAR RIM
Moustache, asymmetric, alloy 6061E, welded, 32 holes, 28", internal width 23mm

FRONT TYRE
Schwalbe, Impac Streetpac, 700x47c

REAR TYRE
Schwalbe, Impac Streetpac, 700x47c

HANDLEBAR
Moustache, ergonomic, alloy, 80mm rise

HEADSET
FSA, No 10P

GRIPS
Ergonomic, dual-density

SADDLE
Selle Royal, Wave

SEATPOST
Moustache, alloy, 31.6mm, 350mm

SEATCLAMP
Moustache, alloy, 31.8mm

FRONT LIGHT
AXA, Blueline, 30 lux, powered by main battery

REAR LIGHT
Spanninga, Presto2Guard, powered by main battery

KICKSTAND
Moustache, adjustable

MUDGUARD
Moustache, alloy, double wall design, w/alloy stays

CARRIER
Moustache, alloy, removable QL3 lateral fixation

PEDALS
Resin platform with reflectors

SIZE
XL

COLOR
Black matt

WEIGHT
22.8 kg

GVWR
135 kg

WARRANTY
5 years frame and fork Moustache Bikes - 2 years motor, battery

Find this bike online

MOUSTACHE

SAMEDI 28.1
2021

SA28C0159215

Samedi 28.1 Open

ST - Taille / Size	mm	390 (S)	450 (M)	510 (L)
Taille utilisateur / User size	m	1,49 - 1,61	1,59 - 1,76	1,74 - 1,90
TT - Tube supérieur / Top tube	mm	550	575	600
RC - Bases / Rear center	mm	470	470	470
HT - Douille de direction / Headtube	mm	140	150	160
WB - Empattement / Wheelbase	mm	1092	1110	1128
FL - Longueur de fourche / Fork length	mm	477	477	477
BB - Hauteur de boitier / BB height	mm	300	300	300
SA - Angle de selle / Seat angle	°	71,4	71,4	71,4
HA - Angle de direction / Head angle	°	67,7	68,1	68,7
Reach	mm	348	366	387
Stack	mm	614	625	637
SO - Enjambement / Standover	mm	688	683	681

Samedi 28.1

ST - Taille / Size	mm	410 (S)	470 (M)	530 (L)	590 (XL)
Taille utilisateur / User size	m	1,55 - 1,70	1,66 - 1,83	1,81 - 1,95	1,90 - 2,05
TT - Tube supérieur / Top tube	mm	560	585	610	636
RC - Bases / Rear center	mm	470	470	470	470
HT - Douille de direction / Headtube	mm	140	150	170	180
WB - Empattement / Wheelbase	mm	1097	1118	1137	1162
FL - Longueur de fourche / Fork length	mm	477	477	477	477
BB - Hauteur de boitier / BB height	mm	300	300	300	300
SA - Angle de selle / Seat angle	°	71,4	71,4	71,4	71,4
HA - Angle de direction / Head angle	°	67,9	68,4	68,9	68,9
Reach	mm	354	375	394	415
Stack	mm	615	627	648	636
SO - Enjambement / Standover	mm	756	785	792	815

Find this bike online

MOUSTACHE