

DIMANCHE 28

ROAD 4 2025

DI28C0458240



Product specifications may change without notice. Non-contractual information.

FRAME Dimanche 28, 6061 T4-T6 alloy, variable thickness hydroformed tubes, CompactTube integration and internal cable routing	CRANKS FSA, forged aluminum, 170mm	SADDLE Selle Royal, SRX
FORK Dimanche 28, full carbon, tapered steerer tube 1"1/8-1"1/2, FlatMount 160mm direct brake mount, 12x100mm axle, 50mm offset, for tires in 700x45, mounts for mudguard	FRONT BRAKE SRAM, Apex, hydraulic disc	SEATPOST Moustache, alloy, 27.2mm, 350mm
MOTOR Bosch, Performance Line SX, Smart System, 60Nm	REAR BRAKE SRAM, Apex, hydraulic disc	SEATCLAMP Moustache, alloy, 34.9mm
BATTERY Bosch, CompactTube 400Wh, Smart System	FRONT ROTOR SRAM, Paceline, 160mm	FRONT LIGHT -
CONDITIONS Maximum distance, calculated for a 70kg rider in ideal conditions. Estimate your battery range .	REAR ROTOR SRAM, Paceline, 160mm	PEDALS alloy platform with reflectors
CHARGER Bosch, 2Ah	FRONT HUB Moustache, 24H, 12x100mm, thru axle	SIZE XL
DISPLAY Bosch, Kiox 300, Smart System	REAR HUB Moustache, 24H, 12x142mm, thru axle	COLOR Pebble grey glossy
REMOTE Bosch, System Controller and Mini Remote, Smart System	FRONT RIM Moustache, al:30, alloy 6061, welded, 24 holes, 700c, 22mm internal width	WEIGHT 16.3 kg
RANGE AUTONOMY 116 km	REAR RIM Moustache, al:30, alloy 6061, welded, 24 holes, 700c, 22mm internal width	GVWR 120 kg
REAR DERAILLEUR SRAM, Apex XPLR, 12-speed	FRONT TYRE Schwalbe, Pro One, 700x34C, SuperRace, TLE	WARRANTY 5 years frame and fork Moustache Bikes - 2 years motor, battery
CHAINRING SRAM, Narrow-Wide, 44 teeth, chainguard	REAR TYRE Schwalbe, Pro One, 700x34C, SuperRace, TLE	
CASSETTE SRAM, XPLR, PG-1231 12-speed, 11-44T	HANDLEBAR Moustache, alloy, Road, drop 105, reach 65, flare 20°, 460mm	
CHAIN Sram, Apex, 12-speed, 120 links	STEM Moustache, 3D forged Aluminum, 90mm	
	HEADSET Acros, AZF-725, sealed bearings, internal routing	
	GRIPS Moustache bar tape	




Find this bike online

{MOUSTACHE

DIMANCHE 28

ROAD 4 2025

DI28C0458240



Dimanche 28 Road 2/4/6 - Dimanche 29 Gravel 2/4/6

ST - Taille / Size	mm	460 (S)	500 (M)	540 (L)	580 (XL)
Taille utilisateur / User size	m	1,53 - 1,68	1,66 - 1,81	1,79 - 1,94	1,92 - 2,07
TT - Tube supérieur / Top tube	mm	545	565	585	605
RC - Bases / Rear center	mm	437	437	437	437
HT - Douille de direction / Headtube	mm	120	135	160	180
WB - Empattement / Wheelbase	mm	1039	1049	1061	1071
FL - Longueur de fourche / Fork length	mm	415	415	415	415
BB - Hauteur de boîtier / BB height	mm	288,5	288,5	288,5	288,5
SA - Angle de selle / Seat angle	°	73,3	73	72,8	72,5
HA - Angle de direction / Head angle	°	70	70,7	71,3	72
Reach	mm	375	386	395	405
Stack	mm	569	586	612	634
SO - Enjambement / Standover	mm	772	800	830	850



Find this bike online

{NOUSTACHE