

DIMANCHE 29

GRAVEL 2 2025

DI29CE254240



Product specifications may change without notice. Non-contractual information.

FRAME Dimanche 29, 6061 T4-T6 alloy, variable thickness hydroformed tubes, CompactTube integration and internal cable routing	FRONT BRAKE Shimano, MT200/UR300, hydraulic disc	SADDLE Selle Royal, VIVO
FORK Dimanche 29, full carbon, tapered steerer tube 1"1/8-1"1/2 - FlatMount 180mm direct brake mount - 12x100mm Axle - 50mm offset - For tires in 700x50 - Mounts for mud-guard and luggage racks	REAR BRAKE Shimano, MT200, hydraulic disc	SEATPOST EXA, 860i, suspension dropper-post w/remote lever, 31.6mm, 75mm
MOTOR Bosch, Performance Line SX, Smart System, 60Nm	FRONT ROTOR Shimano, 180mm	SEATCLAMP Moustache, alloy, 34.9mm
BATTERY Bosch, CompactTube 400Wh, Smart System	REAR ROTOR Shimano, 160mm	FRONT LIGHT Trellock, Lighthammer, 80 lux, powered by main battery
CONDITIONS Maximum distance, calculated for a 70kg rider in ideal conditions. Estimate your battery range .	FRONT HUB Moustache, 24H, 12x100mm, thru axle	REAR LIGHT Spanninga, Presto2Guard, powered by main battery
CHARGER Bosch, 2Ah	REAR HUB Moustache, 24H, 12x142mm, thru axle	KICKSTAND Moustache, adjustable
REMOTE Bosch, Purion 200, Smart System	FRONT RIM Moustache, al:30, alloy 6061, welded, 24 holes, 700c, 22mm internal width	MUDGUARD Moustache, stable and perfect protection thanks to the integrated mudflap
RANGE AUTONOMY 90 km	REAR RIM Moustache, al:30, alloy 6061, welded, 24 holes, 700c, 22mm internal width	CARRIER Moustache, alloy, light, removable QL3 lateral fixation
REAR DERAILLEUR Shimano, CUES, RD-U6000-GS, 10/11-speed	FRONT TYRE Maxxis, Rambler, 700x50C, 120TPI	PEDALS alloy platform with reflectors
CHAINRING FSA, Narrow-Wide, 42 teeth, chainguard	REAR TYRE Maxxis, Rambler, 700x50C, 120TPI	SIZE L
CASSETTE Shimano, CUES, CS-LG300 10-speed, 11-48T	HANDLEBAR Moustache, alloy, 680mm, 12mm rise, 9° backsweep, 5° upsweep	COLOR Sand Storm matt
CHAIN Shimano, LG500, 130 links	STEM Moustache, aluminium, suspended 10-20mm travel, 90mm	WEIGHT 19.2 kg
SHIFTER Shimano, CUES, SL-U6000-10R, 10-speed	HEADSET Acros, AZF-725, sealed bearings, internal routing	GVWR 120 kg
CRANKS Moustache, forged aluminium, 165mm	GRIPS SB3, Ergonomic	WARRANTY 5 years frame and fork Moustache Bikes - 2 years motor, battery




Find this bike online

{MOUSTACHE

DIMANCHE 29

GRAVEL 2 2025

DI29CE254240



Dimanche 28 Road 2/4/6 - Dimanche 29 Gravel 2/4/6

ST - Taille / Size	mm	460 (S)	500 (M)	540 (L)	580 (XL)
Taille utilisateur / User size	m	1,53 - 1,68	1,66 - 1,81	1,79 - 1,94	1,92 - 2,07
TT - Tube supérieur / Top tube	mm	545	565	585	605
RC - Bases / Rear center	mm	437	437	437	437
HT - Douille de direction / Headtube	mm	120	135	160	180
WB - Empattement / Wheelbase	mm	1039	1049	1061	1071
FL - Longueur de fourche / Fork length	mm	415	415	415	415
BB - Hauteur de boîtier / BB height	mm	288,5	288,5	288,5	288,5
SA - Angle de selle / Seat angle	°	73,3	73	72,8	72,5
HA - Angle de direction / Head angle	°	70	70,7	71,3	72
Reach	mm	375	386	395	405
Stack	mm	569	586	612	634
SO - Enjambement / Standover	mm	772	800	830	850



Find this bike online

THOUSTACHE